

IMAGE RECORDING APPARATUS, IMAGE RECORDING METHOD,
STORAGE MEDIUM WHICH STORES COMPUTER-READABLE PROGRAM
AND THE SAME PROGRAM

5 BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to an image
recording apparatus and an image recording method for
recording an image by applying a coloring material on a
10 recording medium in accordance with image data, and
more particularly to an image recording apparatus and
an image recording method which permit recording on
both sides of the recording medium.

Related Background Art

15 With widespread use of a copier, an information
processing apparatus such as a word processor or
computer and a communication apparatus, an inkjet
recording apparatus for recording a digital image by an
inkjet method has rapidly come into wide use as one of
20 output apparatuses for image forming (recording) of the
above apparatuses. In the recording apparatus of this
type, in order to improve a recording speed, a
recording head which has integrated ink discharge ports
and liquid paths is used as a recording head which has
25 a plurality of ink discharge nozzles arranged
integratedly, and recently, with the progress of color
supporting, many of the apparatuses have been equipped

with more than one recording head as above described together.

In an inkjet recording method, the recording is executed by applying ink as recording liquid, in the form of a spattering (or flying) droplet, is applied to a recording medium such as paper, and the method makes a low noise because it is a non-contact method. Further, high concentration of the ink discharge nozzles can cause realization of high resolution and high speed recording, and moreover, no particular processing such as developing or fixing is required to be effected on a recording medium such as a plain paper, and an image of high quality can be obtained at low cost, so that a range of uses of the method has been increased in recent years. Especially, an inkjet recording apparatus of an on-demand type is considered to have a potential for future demand since the apparatus is easily made to be color supporting and can be also miniaturized and simplified in itself. The variety of uses by users has also increased, which has accompanied various types of apparatuses coming into practical use. As an example, there is a recording apparatus including a both-side recording mechanism which permits recording on both sides of a recording medium.

In the recording apparatus including such a both-side recording mechanism, generally, ink is first

applied on a surface (first recording side) of the recording medium to carry out recording on the surface, and then the recording medium is reversed to carry out recording on a reverse side (second recording side).

5 At this time, if recording is carried out on a recording medium with relatively poor permeability of ink, the ink is not immediately permeated and it sometimes takes much time for the ink on the medium surface to be sufficiently dried (or fixed). When
10 carrying out recording on the recording medium with such relatively poor fixing of the ink, it is necessary to set time between recording on the surface and recording on the reverse side relatively long. It is because, if the recording medium is to be reversed to
15 start recording on the reverse side immediately after recording on the surface, the ink on the surface which is not sufficiently dried (or fixed) is made contact with a conveying path due to the above described reversing, and the ink on the surface and the conveying
20 path are rubbed against each other to cause an ink stain. Accordingly, it is preferable to set a length of time between an end of surface recording and a start of reverse side recording such that the ink on the
~~medium surface is sufficiently dried to cause no ink~~
25 stain even if the recording medium is reversed. For example, in Japanese Patent Laid-Open No. 6-134982, a length of time between an end of surface recording and

a start of reverse side recording is determined in accordance with a kind of a recording medium.

According to the Japanese Patent Laid-Open No. 6-134982, a length of time is set relatively short in
5 case of recording on a recording medium which ink permeates relatively quickly and on which the ink is well fixed, while the length of time is set relatively long in case of recording on a recording medium which the ink permeates relatively slowly and on which the
10 ink is poorly fixed, thereby preventing an ink stain.

However, in the Japanese Patent Laid-Open No. 6-134982, the length of time between the end of surface recording and the start of reverse side recording is set in consideration of only the kind of the recording
15 medium, so that the lengths of time are identically set even in case of recording on the same recording media in different printing duties. That is, the same length of time is required in either case of a high printing duty or a low printing duty. The inventor has found
20 that, though acceptable in the case of the high printing duty, a time longer than need is set in the case of the low printing duty, which causes a waste of time. That is, in the case of the low printing duty,
~~the ink is fixed more quickly than in the case of the~~
25 high printing duty, so that occurrence of an ink stain can be sufficiently restrained even if the time is set short.

As described above, conventionally, reduction of printing time in the case of the low duty has not been sufficiently achieved due to identically setting the time between the end of surface recording and the start of reverse side recording regardless of the printing duty. Under the present circumstances where high speed and high quality are required more and more, it is desirable to eliminate a waste of time to achieve reduction of printing time and to sufficiently restrain occurrence of an ink stain.

SUMMARY OF THE INVENTION

The present invention is achieved in view of the above problems and has its object to provide an image recording apparatus, an image recording method, a storage medium which stores a computer-readable program and the program, which can restrain occurrence of an ink stain and achieve reduction of time for printing in the case of both-side recording.

In order to achieve the above object, the present invention provides an image recording apparatus for recording an image by applying a coloring material on a recording medium in accordance with image data by

recording means, including: conveying means for conveying the recording medium so as to permit recording on both of a first recording side and a second recording side of the recording medium; setting

means for variably setting a length of time between an
end of recording on the first recording side of the
recording medium and a start of recording on the second
recording side of the recording medium in accordance
5 with the image data for recording on the first
recording side of the recording medium; and control
means for controlling conveying operation by the
conveying means such that recording on the second
recording side of the recording medium by the recording
10 means is started after passage of time set by the
setting means.

The present invention further provides an image
recording apparatus for recording an image by applying
a coloring material on a recording medium in accordance
15 with image data by recording means, including:
conveying means for conveying the recording medium so
as to permit recording on both of one recording side
and the other recording side of the recording medium;
determining means for determining on which recording
20 side of one recording side or the other recording side
of the recording medium, recording is previously
carried out, based on both of image data for recording
on one recording side of the recording medium and image
~~data for recording on the other side of the recording~~
25 medium; setting means for variably setting a length of
time between an end of recording on one recording side
of the recording medium and a start of recording on the

other recording side of the recording medium in accordance with the image data for recording on the recording side which is determined by the determining means; and control means for controlling conveying operation by the conveying means such that recording on the other recording side by the recording means is started after passage of time set by the setting means.

The present invention further provides an image recording method for recording an image by applying a coloring material on a recording medium in accordance with image data by recording means, including: a conveying process of conveying the recording medium so as to permit recording on both of a first recording side and a second recording side of the recording medium; a setting process of variably setting a length of time between an end of recording on the first recording side of the recording medium and a start of recording on the second recording side of the recording medium in accordance with the image data for recording on the first recording side of the recording medium; and a controlling process of controlling conveying operation of the recording medium such that recording on the second recording side of the recording medium by the recording means is started after passage of time set by the setting means.

The present invention further provides an image recording method for recording an image by applying a

coloring material on a recording medium in accordance with image data by recording means, including: a conveying process of conveying the recording medium so as to permit recording on both of one recording side and the other recording side of the recording medium; a determining process of determining on which recording side of one recording side or the other recording side of the recording medium, recording is previously carried out, based on both of image data for recording on one recording side of the recording medium and image data for recording on the other side of the recording medium; a setting process of variably setting a length of time between an end of recording on one recording side of the recording medium and a start of recording on the other recording side of the recording medium in accordance with the image data for recording on the recording side which is determined by the determining process; and a controlling process of controlling conveying operation of the recording medium such that recording on the other recording side by the recording means is started after passage of time set by the setting process.

The present invention further provides a computer-readable storage medium which stores a program for
executing a control processing of an image recording apparatus for recording an image by applying a coloring material on a recording medium in accordance with image

data by recording means, wherein the program comprises:

- (a) a process of conveying the recording medium so as to permit recording on both of a first recording side and a second recording side of the recording medium;
- 5 (b) a process of variably setting a length of time between an end of recording on the first recording side of the recording medium and a start of recording on the second recording side of the recording medium in accordance with the image data for recording on the
- 10 first recording side of the recording medium; and (c) a process of controlling conveyance of the recording medium such that recording on the second recording side of the recording medium by the recording means is started after passage of time set by the setting
- 15 process.

The present invention further provides a program for executing a control processing of an image recording apparatus for recording an image by applying a coloring material on a recording medium in accordance

20 with image data by recording means, comprising: (a) a process of conveying the recording medium so as to permit recording on both of a first recording side and a second recording side of the recording medium; (b) a

25 ~~process of variably setting a length of time between an~~
end of recording on the first recording side of the recording medium and a start of recording on the second recording side of the recording medium in accordance

with the image data for recording on the first
recording side of the recording medium; and (c) a
process of controlling conveyance of the recording
medium such that recording on the second recording side
5 of the recording medium by the recording means is
started after passage of time set by the setting means.

By providing a first configuration wherein time
(waiting time) between an end of surface recording and
a start of reverse side (second recording side)
10 recording is variably set based on image data on the
surface (first recording side), the waiting time is set
short when a recording duty of the surface is low,
which permits sufficiently reducing an ink stain and
also achieving reduction of total recording time in
15 both-side recording.

Further, by providing a second configuration
wherein recording is started on either of the surface
(first recording side) or the reverse side (second
recording side) which has a lower recording duty, and
20 wherein based on the recording data on the previous
recording side, waiting time between an end of
recording on the previous recording side and a start of
recording on the reverse side is variably set, the
~~waiting time can be reduced more than in the case of~~
25 the above described first configuration, which results
in realizing further reduction of recording time in
both-side recording.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic view of a configuration of an example of a recording apparatus which can be applied to the present invention;

5 FIG. 2 is a perspective view of a peripheral configuration of a recording section 2 in the image recording apparatus in FIG. 1;

FIG. 3 is a typical perspective view of a column of ink discharge ports in an ink discharge portion of an inkjet recording head 21 seen from a recording
10 medium side;

FIG. 4 is a typical perspective view of a part of inner structure of the ink discharge portion;

FIG. 5 is a block diagram showing a control system
15 of an image recording apparatus according to a first embodiment of the present invention;

FIG. 6 is an explanatory view of a buffer memory of a recording apparatus;

FIG. 7 is another explanatory view of the buffer
20 memory of the recording apparatus;

FIG. 8 is a flowchart showing a flow of recording operation at the time of a both-side recording mode;

FIG. 9 is a table showing relationship between
ranges of application amounts of ink (M) and lengths of
25 time (T) between an end of surface recording and a start of reverse side recording;

FIG. 10 is a flowchart showing control operation

of the recording apparatus; and

FIG. 11 is a table showing relationship among kinds of recording media, ranges of application amounts of ink (M) and lengths of time (T) between an end of surface recording and a start of reverse side recording.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiments of the present invention will be described below with reference to the drawings.
(First Embodiment)

FIG. 1 is a schematic view of a configuration of an example of an image recording apparatus which can be applied to the present invention and which is provided with a both-side recording mechanism (both-side printing function) for permitting recording on both sides of a recording medium by reversing the recording medium. In FIG. 1, reference numeral 1 denotes a paper feed tray (paper feed section); 2, a recording section (recording means); 3, a paper output tray (paper output section); 4, a both-side tray; 5 and 6, change-over sections; and 7, a conveying path. Located on the paper feed tray 1 are the recording media, which are fed one by one. On the fed recording medium, an image is formed (recorded) by the recording section 2 and output to the paper output tray 3 as it is in the case of one-side recording. In the case of both-side

recording, the change-over section 5 is pivoted upward in the figure (substantially in the same direction as an A direction in FIG. 1) to switch the conveying path 7, and the recording medium with recording on one side by the recording section 2 is conveyed to the both-side tray 4 to be temporarily stored.

A length of time between an end of recording on a surface (first recording side) of the recording medium and a start of recording on a reverse side (second recording side) is determined (set) in accordance with an image data on the surface. That is, a length of time required for sufficient fixing (or drying) of ink is determined in consideration of the image data, and reverse side recording is adapted to be started after passage of the determined time. In this embodiment, the recording medium is in wait in the both-side tray 4 after the end of surface recording and before the start of reverse side recording. For this reason, the time between the end of surface recording and the start of reverse side recording is sometimes referred to as "waiting time" herein.

When recording on the reverse side, the change-over section 6 is pivoted downward in the figure (substantially in the same direction as a B direction in FIG. 1) to switch the conveying path and to feed the recording medium from the both-side tray 4. The recording medium is then conveyed to the recording

section 2 through the conveying path at a point F.
After that, recording on the reverse side is carried
out in the recording section 2, and the recording
medium with recording on the reverse side is output to
5 the paper output tray 3 as it is. The recording medium
output from the both-side tray 4 is conveyed to the
recording section 2 through the point F in the figure,
so that the surface and reverse side of the recording
medium are changed when the recording medium reaches a
10 position (point B) facing the recording section 2,
which permits recording on the reverse side by the
recording section 2. By a mechanism configured by the
both-side tray 4, the change-over section 6 and the
conveying path 7 including the point F, the recording
15 medium is reversed to permit both-side recording, thus
the mechanism is hereinafter referred to as a reversing
mechanism (reversing means) or a both-side recording
mechanism.

Here, conveying manners of the recording medium in
20 the case of one-side recording and the case of both-
side recording will be illustrated using reference
characters A to F showing positions in FIG. 1. In one-
side recording, the recording medium is conveyed in the
order of A → B → C. ~~In both-side recording, the~~
25 recording medium is conveyed in the order of A → B → D
→ E → F → B → C.

FIG. 2 is a perspective view of a peripheral

configuration of the recording section 2 in the image recording apparatus in FIG. 1. A recording section (inkjet unit) 11 having a column (or row) of discharge ports for discharging ink is located on a carriage 13.

5 The recording medium made of a plain paper or an OHP sheet is supported by a paper output roller 17 in a sandwiched manner through an conveying roller (not shown) and conveyed in an arrow direction by driving an unshown conveying motor. The carriage 13 is supported
10 in a guided manner by a guide shaft 12 and an encoder (not shown). The carriage 13 is reciprocated along the guide shaft 12 by driving a carriage motor 15 via a driving belt 14. That is, the carriage is reciprocated in a Y direction in FIG. 2.

15 A heat-generating element (electrothermal energy transducing element) for generating thermal energy for discharging ink is provided inside (in a liquid path) of an ink discharge portion of an inkjet recording head (details thereof will be described below with reference
20 to FIGS. 3 and 4) in the inkjet unit 11. In compliance with reading timing of the encoder (not shown), the heat-generating element is driven based on a recording signal to spatter and apply an ink droplet on the
~~recording medium and to thereby form an image.~~

25 Arranged on a home position (HP) outside a recording area is a recovery unit having a cap 16. When recording is not carried out, the carriage 13 is

moved to the home position (HP), and an ink discharge
ports forming side of the inkjet recording head is
closed by the cap 16 to prevent adhesion of the ink
resulting from vaporization of an ink solvent or
5 clogging by applied foreign matters such as dust or
powdered paper.

The cap 16 having a capping function is used, in
order to solve discharge failure or clogging due to
increased thickness, adhesion, or the like of the ink
10 at the ink discharge port with low recording frequency,
as a position for carrying out a preliminary discharge
mode wherein the ink is discharged to the cap 16 apart
from the ink discharge port or as a position for
carrying out a sucking operation mode wherein an
15 unshown pump is operated with the cap on to suck the
ink from the ink discharge port and to recover the ink
discharge port with the discharge failure. Providing a
blade in a position adjacent to the cap 16 permits
cleaning the ink discharge ports forming side of the
20 inkjet recording head.

FIG. 3 is a typical perspective view of a column
of the ink discharge ports in the ink discharge portion
of an inkjet recording head 21 seen from the recording
medium side, and ~~FIG. 4 is a typical perspective view~~
25 of a part of inner structure of the ink discharge
portion. The ink discharge portion includes an ink
discharge port side 22 having a plurality of ink

discharge ports 23, and in liquid paths 31 communicating with the ink discharge ports 23, energy generating elements 32 for generating energy which is required for discharging the ink are respectively
5 arranged. An arrow Y in FIG. 3 shows a scanning direction of the carriage 13. Reference numeral 33 in FIG. 4 denotes a sensor for detecting temperature of the recording head, and in this embodiment, thermistors 33 are provided on both ends of the column of the
10 discharge ports. Temperature detecting means is not limited to this, but other sensor such as a diode sensor or the like may be used, and further, the temperature of the head may be calculated from a duty of printing dots.

15 As shown in FIG. 4, a recording method wherein the ink is discharged utilizing the thermal energy is used. However, the embodiment is not limited to this recording method. For example, a pressure control method for discharging an ink droplet from an orifice
20 (discharge port) by mechanical vibration of a piezo-vibration element is applicable in an on-demand type, and a charge control method, a diffusion control method, or the like are applicable in a continuous
type.

25 Next, a configuration of a control system in the image recording apparatus shown in FIG. 1 will be described. A configuration of the control system is

shown in a block diagram in FIG. 5. A CPU 130, ROM 131, RAM 132, a recording head moving drive section 133, a recording medium conveying drive section 134, a recording head recording drive section 135, a data receiving section 136, a waiting time timer section 137 and an interface section 138 are connected via a data bus 141. The CPU 130 controls the whole recording apparatus 144 based on a program stored in the ROM 131. Recording information transmitted from a host computer 140 via a printer driver 139 is received by the data receiving section 136 on a printer side. The data receiving section 136 sends and receives data in accordance with condition of the printer and the received data is stored in the RAM 132. In compliance with a recording command from the host computer 140, the CPU 130 controls the recording head moving drive section 133, the recording medium conveying drive section 134 and the recording head recording drive section 135.

Further detailed description on FIG. 5 will be made. The CPU 130 reads programs or various kinds of data from the ROM 131, the RAM 132, or the like, carries out necessary calculation or determination, and outputs various control signals in compliance with control programs to carry out drive control of the whole apparatus. The ROM 131 is a program memory and stores various programs, various data or the like for

the CPU 130 to operate. The RAM 132 is a buffer memory and is configured by a working area where the CPU 130 temporarily stores the data on command or calculation results, a text area where various data is stored, or
5 the like. To the CPU 130, the waiting time timer section 137 which measures time based on an instruction signal from the CPU 130 and outputs time information is connected via the data bus 141.

The CPU 130 is electrically connected to the host
10 computer 140 via the interface section 138, and controls recording operation based on an image data (recording data) from the host computer 140, which is stored in the ROM 131 or RAM 132. The host computer 140 is provided with the printer driver 139 for
15 receiving recording information generated or edited on the computer and passing the information to the recording apparatus 144 side via the interface section 138. The printer driver 139 is provided such as to be able to set or select various information on recording
20 of the recording apparatus 144, and the set or selected information is also passed to the recording apparatus 144 side.

Various information on recording includes setting
of a kind of the recording medium such as a sheet for
25 recording, or selecting between a one-side recording mode or both-side recording mode, as an example. The CPU 130 controls the recording head moving drive

section 133 and recording medium conveying drive
section 134, and also controls the recording section 2
(recording head 21) via a recording head recording
drive section 135 based on the recording information
5 stored in the RAM 132. An operation panel for setting
recording condition of the recording mode or the like
and a sheet sensor for detecting front and rear ends of
the recording sheet are connected to the CPU via the
data bus.

10 The RAM 132 as the buffer memory is adapted to
store the recording data for one scanning or plural
times of scanning. This line buffer is a buffer which
stores information regarding the position in the
recording area where recording is carried out by the
15 orifice of the recording head in one main scanning of
the recording head. FIGS. 6 and 7 show an example of a
condition where the recording data is stored in the
buffer provided in the RAM 132.

The buffer is configured to have M columns
20 required for expressing the maximum recording width of
the recording sheet, which can be used by the recording
apparatus 144, with a predetermined dot pitches and
lines corresponding to the number of orifices of the
recording head. ~~For the recording data transmitted~~
25 from the host computer and expanded, storing a dot
information is started at the first line and first
column (the dot filled in with black) of the buffer as

shown in FIG. 6 when recording on the surface of the recording sheet, while storing a dot information is started at line H and column M (the dot filled in with black) of the buffer as shown in FIG. 7 when recording
5 on the reverse side. In case of storing the recording data on the reverse side, storing order may be the same as in the case of storing on the surface shown in FIG. 6, and may be configured to reverse order of the image data (recording data) passed from the printer driver
10 139 to the recording apparatus 144 side as shown in FIG. 5. The dots shown in FIG. 6 are such that the dots expanded and recorded on the recording sheet are typically represented, and a dot is not necessarily dealt with as a piece of recording data.

15 Next, operation of the inkjet recording apparatus according to this embodiment at the time of the both-side recording mode will be described based on the control system configured as mentioned above. The recording apparatus is configured such that the
20 recording data stored in the line buffer (RAM 132) for recording is subjected to a predetermined processing for both-side recording in the printer driver 139 and then passed via the interface section 138.

FIG. 8 is a flowchart showing a flow of recording
25 operation at the time of the both-side recording mode. In a step S1, a command of start of recording is received from the host computer 140. Next, in a step

S2, an image data is received from the printer driver 139 of the host computer 140. Then, in a step S3, a length of time (waiting time) between an end of recording on the surface (first recording side) of the recording medium and a start of recording on the reverse side (second recording side) is calculated to be set (determined) based on the received image data. Here, the time is determined in accordance with the image data for recording on the surface (first recording side) of the recording medium. Specifically, an application amount of ink (total amount of applied ink) on the surface is calculated from the image data for recording on the surface, and based on the calculation result, the time between the end of surface recording and the start of reverse side recording is determined. For example, when the application amount of ink is a first amount, a first length of time is set, while when the application amount of ink is a second amount smaller than the first amount, a second length of time shorter than the first length of time is set. That is, the larger application amount of ink causes the longer length of time, while the smaller application amount of ink causes the shorter length of time.

25 Next, in a step S4, recording on the surface of the recording medium is carried out. Then, in a step S5, a timer is set for the time set in the step S3.

Subsequently, in a step S6, conveyance of the recording medium is restarted after having the recording medium wait for a certain time so that the reverse recording is started after passage of the set time. In a step
5 S7, recording on the reverse side of the recording medium is carried out. After the end of recording on the reverse side, the recording medium is output to the paper output tray (paper output section) 3. As described above, both-side recording is ended (a step
10 S8).

In the above description, the application amount of ink (total amount of applied ink) on the surface (first recording side) of recording medium is calculated, and in accordance with the calculation
15 results, the time between the end of recording on the surface (first recording side) of the recording medium and the start of recording on the reverse side (second recording side) is determined. However, the embodiment is not limited to this. For example, the length of
20 time may be determined (set) in accordance with the number of application of ink on the surface (first recording side) of the recording medium. In this case, when the number of application of ink is a first
~~number, a first length of time is set, while when the~~
25 number of application of ink is a second number smaller than the first number, a second length of time shorter than the first length of time is set. That is, the

larger number of application of ink causes the longer length of time, while the smaller number of application of ink causes shorter length of time. The length of time may be determined (set) in accordance with a recording duty of recording on the surface (first recording side) of the recording medium. In this case, when the recording duty is a first duty, a first length of time is set, while when the recording duty is a second duty lower than the first recording duty, a second length of time shorter than the first length of time is set. That is, the higher recording duty causes the longer length of time, while the lower recording duty causes the shorter length of time. Here, the recording duty means, for example, a ratio of the number of dots formed in a predetermined area on the recording medium. The length of time may be determined (set) in accordance with an amount of data for applying ink of the image data for recording on the surface (first recording side) of the recording medium. In this case, when the amount of data for applying ink is a first amount, a first length of time is set, while when the amount of data is a second amount smaller than the first amount, a second length of time shorter than the first length of time is set. That is, the larger amount of data for applying ink causes the longer length of time, while the smaller amount of data for applying ink causes the shorter length of time.

As described above, in this embodiment, a time interval between recording on the first recording side (surface) of the recording medium and recording on the second recording side (reverse side) is determined in accordance with the image data. Further, in this embodiment, by variably setting time for having the recording medium wait in the both-side tray 4, the time interval between recording on the first recording side (surface) of the recording medium and recording on the second recording side (reverse side) is set as the determined time interval described above.

Specifically, the time for having the recording medium wait in the both-side tray 4 is set so as to correspond to the determined time interval.

A relationship between the length of time (T) between the end of recording on the surface (first recording side) of the recording medium and the start of recording on the reverse side (second recording side) and the application amount of ink (M) may be previously stored in a waiting time determining table, and the time may be determined by reading from the table. For example, a table is prepared, as shown in FIG. 9, where ranges of the application amounts of ink (M): $0 \leq M < m_1$, $m_1 \leq M < m_2$, $m_2 \leq M < m_3$, $m_3 \leq M$ ($0 < m_1 < m_2 < m_3$) are

corresponded with the length of time (T): $T=t_1$, $T=t_2$, $T=t_3$, $T=t_4$ ($t_1 < t_2 < t_3 < t_4$), and the length of time may be obtained by referring to the table. That is, when the

range of the application amount of ink (M) is $0 \leq M < m_1$,
the length of time (T) may be set at t_1 ; when the range
of the application amount of ink (M) is $m_1 \leq M < m_2$, the
length of time may be set at t_2 ; when the range of the
5 application amount of ink (M) is $m_2 \leq M < m_3$, the length of
time may be set at t_3 ; and when the range of the
application amount of ink (M) is $m_3 \leq M$, the length of
time may be set at t_4 .

There may be prepared a table which represents a
10 relationship between the length of time and the number
of application of ink, a table which represents a
relationship between the length of time and the
recording duty, and a table which represents a
relationship between the length of time and the amount
15 of data for applying ink, or the like.

The above descriptions have been made with respect
to the fact that the length of time (T) between the end
of recording on the surface (first recording side) of
the recording medium and the start of recording on the
20 reverse side (second recording side) is determined in
accordance with the image data. However, the
embodiment is not limited to this. In addition to the
image data, a kind of the recording medium may be
~~considered as an element of determining the length of~~
25 time (T). In this case, a relationship among the
length of time (T), the application amount of ink (M)
and the kind of the recording medium may be previously

stored as a waiting time determining table, and the length of time (T) may be determined by reading from the table. An example of the table is shown in FIG. 11. Use of such a table even allows a property of the recording medium to be considered, which permits setting the length of time (T) more suitable to the property of each recording medium. Further, total recording time can be reduced more than the case in the Japanese Patent Laid-Open No. 6-134982 where the length of time (T) is set only in accordance with the kind of the recording media.

In this embodiment, the recording apparatus carries out determining the length of time between the end of surface recording and the start of reverse side recording. However, not limited to this, the printer driver may carry out the determination.

As described above, in this embodiment, the length of time between the end of surface recording and the start of reverse side recording is variably set in accordance with the image data on the surface of the recording medium, so that occurrence of an ink stain can be sufficiently restrained and total recording time in both-side recording can be reduced.

(Second Embodiment)

Next, a second embodiment will be described. The second embodiment is identical to the first embodiment except for the control operation of the recording

medium, thus descriptions on other components will be omitted here. That is, FIG. 8 only is different, and FIGS. 7 and 9 can be applied to this embodiment.

FIG. 10 is a flowchart showing the control operation of the recording apparatus. In FIG. 10, a command of start of recording from the host computer 140 is received (step S20). Next, when an image data from the host computer 140 is received (step S21), the CPU 130 of the recording apparatus 144 compares the image data on the first recording side with the image data on the second recording side and determines a recording side for previous recording (step S22). Specifically, a side with smaller application amount of ink is determined to be a previous recording side. Here, the first recording side is the previous recording side. Previous recording on the side with the smaller application amount of ink (with lower recording duty) can reduce the length of time between the end of surface recording and the start of reverse side recording.

Next, based on the application amount of ink on the previous recording side (first recording side), the length of time between the end of surface recording and the start of reverse side recording is determined (set) (step S23). Going to a step S24, recording on the previous recording side (first recording side) is carried out. Then, in a step S25, a timer is set for

the time set in the step S23. Subsequently, in a step S26, conveyance of the recording medium is restarted after having the recording medium wait for a certain time so that the reverse recording is started after
5 passage of the set time. In a step S27, recording on the reverse side of the recording medium is carried out. After the end of recording on the reverse side, the recording medium is output to the paper output tray (paper output section) 3. As described above, both-
10 side recording is ended (a step S28).

In the above description, the side with the smaller application amount of ink is determined to be the previous recording side. However, not limited to this, for example, a side with the smaller number of
15 application of ink may be determined to be the previous recording side, a side with a smaller recording duty may be determined to be the previous recording side, or a side with a smaller amount of data for applying ink may be determined to be the previous recording side.
20 As described above, in this embodiment, based on both of the image data for recording on one recording side (first recording side) of the recording medium and the image data for recording on the other recording side
~~(second recording side) of the recording medium, it is~~
25 determined on which recording side of one recording side (first recording side) or the other recording side (second recording side) of the recording medium,

recording is previously carried out.

For a method of determining the length of time between the end of surface recording and the start of reverse side recording, the same method as in the first embodiment can be used.

In this embodiment, the recording apparatus carries out determining the previous recording side of the first and second recording sides and the length of time between the end of surface recording and the start of reverse side recording. However, not limited to this, the printer driver may carry out the determination.

As described above, in this embodiment, recording is started on the side with the lower recording duty of the first and second recording sides and based on the recording data of the previous recording side, the length of time between the end of recording on the previous recording side and the start of recording on the reverse side is determined, so that the time can be reduced and the total recording time in both-side recording can be further reduced.

(Third Embodiment)

Next, a third embodiment will be described. In ~~the first and second embodiments, the length of time~~ between the end of recording on the first recording side and the start of recording on the second recording side is controlled by variably setting the time for

having the recording medium wait in the both-side tray.
However, in the third embodiment, the length of time is
controlled by variably setting a conveying speed of the
recording medium. That is, the length of time is first
5 determined based on the image data on the first
recording surface, and when the determined time is
relatively long, the conveying speed is set "low", and
when the determined time is relatively short, the
conveying speed is set "high", thereby controlling the
10 length of time.

Specifically, a table is prepared where ranges of
the length of time (T): $0 \leq T < t_1$, $t_1 \leq T < t_2$, $t_2 \leq T < t_3$, $t_3 \leq T$
($0 < t_1 < t_2 < t_3$) are corresponded with the conveying speed
(V): $V = v_1$, $V = v_2$, $V = v_3$, $V = v_4$ ($v_1 > v_2 > v_3 > v_4$), and the
15 conveying speed (V) which corresponds to the length of
time (T) may be selected. That is, when the range of
the length of time (T) is $0 \leq T < t_1$, the conveying speed
(V) may be set at v_1 ; when the range of the length of
time (T) is $t_1 \leq T < t_2$, the conveying speed (V) may be set
20 at v_2 ; when the range of the length of time (T) is
 $t_2 \leq T < t_3$, the conveying speed (V) may be set at v_3 ; and
when the range of the length of time (T) is $t_3 \leq T$, the
conveying speed (V) may be set at v_4 . The control of
~~the conveying speed (V) is realized by variably setting~~
25 a rotational speed of a conveying roller provided in a
conveying path.

(Other Embodiments)

In each of the above embodiments, the length of time between the end of recording on the first recording side and the start of recording on the second recording side is variably controlled by variably
5 setting the time for having the recording medium wait in the both-side tray or by variably setting the conveying speed of the recording medium. However, the present invention is not limited to these methods, and it is essential only that the length of time can be
10 variably controlled. For example, the control may be carried out by having the recording medium wait in the conveying path other than the both-side tray, where the waiting time is variably set, or by providing a plurality of conveying paths in the apparatus to switch
15 the paths for conveyance.

Each embodiment of the present invention is achieved by the fact that a storage medium which stores a program code of software for realizing the function of the embodiment described above is supplied to a
20 system or an apparatus and that a computer (or CPU or MPU) of the system or apparatus reads and executes the program code stored in the storage medium.

In this case, the program code itself read from
~~the storage medium realizes the function of the above~~
25 described embodiment, so that the storage medium which stores the program code is to constitute the present invention.

The storage medium for supplying the program code includes, for example, a floppy disk, hard disk, optical disk, magneto-optical disk, CD-ROM, CD-R, magnetic tape, nonvolatile memory card or ROM.

5 It is not needless to say that executing the program code read by the computer realizes the function of the embodiment, and further that, based on an instruction of the program code, an OS (operation system) which operates on the computer carries out a
10 part or all of actual processing, thereby realizing the function of the embodiment.

 Moreover, it is needless to say that the program code read from the storage medium is written in a memory provided in a feature expansion board inserted
15 in the computer or a feature expansion unit connected to the computer, and then that based on the instruction of the program code, the CPU or the like provided in the feature expansion board or feature expansion unit carries out a part or all of actual processing, thereby
20 realizing the function of the embodiment described above.

 The above descriptions have been made with respect to the example of using the inkjet recording method as
~~the recording method.~~ However, there is no need to
25 limit the recording method of the present invention to the inkjet recording method, and a thermal transfer recording method, thermal recording method, and

further, a recording method such as a wire dot recording method and other recording methods are applicable. Further, there is no need to limit to a serial recording method, and "a line recording method" may be used.

The present invention has excellent effects in a recording apparatus which uses a recording head of an inkjet method for carrying out recording by utilizing thermal energy to form a spattering (or flying) droplet, particularly of the inkjet recording methods.

For the typical configuration and principle thereof, it is preferable to use basic principles disclosed in, for example, U.S. Patent No. 4,723,129 and U.S. Patent No. 4,740,796. The method is applicable to both of "an on-demand type" and "a continuous type". Especially in the case of the on-demand type, it is effective because, by applying at least one driving signal, which corresponds to recording information and provides temperature rise more rapid than nucleate boiling, on an electrothermal converting element arranged so as to correspond to a sheet or a liquid path which holds liquid (ink), the electrothermal converting element generates thermal energy, and film boiling occurs on a heat actuating side of a recording head, and consequently, a bubble in the liquid (ink) can be formed which corresponds to the driving signal one to one. By expansion and

contraction of the bubble, the liquid (ink) is discharged through a discharge opening to generate at least one droplet. The driving signal in the form of a pulse is more preferable since suitable expansion and contraction of the bubble are immediately carried out, which permits achieving discharge of the liquid (ink) with especially excellent response. A suitable driving signal in the form of the pulse is such as disclosed in U.S. Patent No. 4,463,359 or U.S. Patent No. 4,345,262. Adopting a condition disclosed in U.S. Patent No. 4,313,124 of the invention regarding a rate of temperature rise of the heat actuating side permits further excellent recording.

The present invention includes, as a configuration of the recording head, a configuration of a combination of the discharge port, liquid path and electrothermal converting element (a line liquid path or rectangular liquid path) disclosed in each of the above s, and also includes a configuration using U.S. Patent No. 4,558,333 and U.S. Patent No. 4,459,600 each of which discloses a heat actuating portion arranged in a bending area.

Moreover, the present invention is effective in a ~~configuration-based on Japanese Patent Laid-Open No.~~ 59-123670 which discloses a configuration such that a plurality of electrothermal converting elements have common slits as discharge portions or Japanese Patent

Laid-Open No. 59-138461 which discloses a configuration such that an opening which absorbs a pressure wave of thermal energy is corresponded with a discharge portion. That is, whatever type the recording head is,
5 the present invention can assure efficient recording.

The present invention is effectively applicable to a full-line type recording head having a length corresponding to the maximum width of a recording medium on which a recording apparatus can carry out
10 recording. Such a recording head may includes either of a configuration such that a plurality of recording heads are combined to meet the length or a configuration as a recording head integrally formed.

Further, the present invention is also effective
15 in the serial type recording head as mentioned above, a recording head secured to an apparatus body, a replaceable tip type of recording head which is mounted on an apparatus body to thereby permit electrical connection with the apparatus body or supply of ink
20 from the apparatus body, and a cartridge type of recording head which per se is integrally provided with an ink tank.

As a configuration of the present recording
~~apparatus, adding discharge recovery means, preliminary~~
25 auxiliary means, or the like of the recording head is preferable since the effect of the present invention can be more stable. Specifically, capping means of the

recording head, cleaning means, pressure or suction means, preliminary heating means for heating by means of an electrothermal transducing element or other heating element or a combination thereof, and
5 preliminary discharge means for discharge other than recording can be cited.

For the kinds and number of equipped recording heads, more than two heads may be provided corresponding to a plurality of inks with different
10 recording colors or concentration. That is, for example, the present invention is also highly effective in a recording apparatus having, besides a recording mode of a main color such as black, at least one of a multi color mode with different colors and a full color
15 mode by mixing colors, in which the recording head may be configured as an integral head or as a combination of a plurality of recording heads.

Moreover, in the embodiments of the present invention described above, the ink is liquid. However,
20 ink which is hardened at room temperature and less and which is softened or liquefied at room temperature may be used. Alternatively, ink which is liquefied at the time of applying a use recording signal may be used
~~since in a general inkjet method, temperature of the~~
25 ink itself is adjusted within a range between 30°C and 70°C to control the temperature such that viscosity of the ink falls within a stable discharge range.

Further, ink which is hardened in an left condition and liquefied by heating may be used in order to positively prevent temperature rise due to thermal energy by using the thermal energy as energy for

5 changing condition of the ink from solid to liquid or prevent vaporization of the ink. In any case, the present invention is applicable in the case of using ink, which has a characteristic of being first

10 liquefied by applying the thermal energy, such as ink liquefied by applying the thermal energy in accordance with the recording signal to discharge liquid ink or ink which is started to be hardened at the time of reaching the recording medium. The ink in these cases may be such as to face an electrothermal converting

15 element in a condition of being held as liquid or solid by a recess of a porous sheet or a through hole as disclosed in Japanese Patent Laid-Open No. 54-56847 or Japanese Patent Laid-Open No. 60-71260. In the present invention, the method most effective to each ink

20 described above is the type of carrying out the film boiling.

As described above, according to the present invention, when carrying out both-side recording,

~~occurrence of an ink stain can be restrained and time~~

25 for printing can be reduced.